

TECHNICAL DATA SHEET

Safety and Function Tester HandHeld

Revision 1.5, September 2025.

Basic unit

ELECTRICAL SPECIFICATIONS

Supply voltage	230 V AC $\pm 10\%$
Mains frequency	50 Hz / optional 60 Hz
Current consumption no-load	0.2 A, fuse T2A

GENERAL SPECIFICATIONS

Display	7 segment, 4 digit
Signal-LEDs	Four test-method LEDs at front panel / PE, IR, LKC, FCT Four measuring-unit LEDs at front panel / s, V, A, Ω Three condition LEDs at front panel / yellow = test in progress, green = result GO, red = result NO GO
Acoustic message	Signaling device for acoustic messages Short signal = result GO, three short signals = result NO GO
Input	Via push buttons at the front panel of the device
Test-result storage	128 test results incl. all default values, measured values, per test step
Test connections	Test socket ¹⁾ on top of the device Two test probe inlets at the rear panel of the device
Communication interface	At the rear panel of the device RS232
Adjustment	Adjustment via software; no need to open the testing device
Software usability	To avoid incorrect entries, all inputs are subject to a plausibility check.
Language on front panel	EN
Development and production	Made in Germany

MECHANICAL SPECIFICATIONS

Mechanical designs	Table-top unit with rubber feet Incl. attachment points for carrying straps Optional: solid mounting feet allowing to tilt the testing device Optional: carrying straps
Operating environment	Operating temperature 0 – 50 °C / 32 – 104 °F, designed for a relative humidity of 0 – 80 %rH without condensation!
Storage	Storing temperature -10 – 60 °C / 14 – 140 °F, designed for a relative humidity of 0 – 90 %rH without condensation!
Dimensions, if only PE/GB and IR	195 x 195 x 70 mm (7.68" x 7.68" x 2.76") (W x D x H)
Dimensions, if additional HVDC, function or leakage current	195 x 295 x 70 mm (7.68" x 11.61" x 2.76") (W x D x H)
Weight	3 kg (6.61 lbs)
Housing color	black

1) The layout of the test connections depends on the device variant.

PE/GB resistance test AC

TEST CURRENT AC

Test current	10 A AC
Frequency	50 Hz, depending on the mains supply / optional 60 Hz
Current regulation	Automatic electronic constant-current regulation with minimum-current monitoring and power-failure detector
Adjustment	Default current approx. + 0.5 A

VOLTAGE

Test voltage max.	12 V AC
-------------------	---------

RESISTANCE

Precision	Accurate 4-wire resistance measurement
Total measuring range	0 – 700 mΩ, depending on the flowing test current and the allowed maximum test voltage 0 – 20 Ω especially for measurements on wind-power stations
resolution	1 mΩ or 1 mV
Resistance measurement from - to	0 – 700 mΩ at 12 V and 10 A 0 – 20 Ω at 12 V and 0.6 A
Measurement accuracy	±1 % of final value, ±10 mΩ

EVALUATION

Evaluation related to	Resistance or voltage drop
Upper resistance limit PE _{Rmax} Or alternatively upper voltage limit PE _{Umax}	0 – 700 mΩ freely definable, test values equal to or smaller than this limit are GO 0 – 7 V freely definable, test values equal to or smaller than this limit are GO
Undercurrent	If the test current is smaller than the default value during the test, the test result is NO GO.

GENERAL INFORMATION

Test timer	0.1 – 1.5 s in steps of 0.1 s
Measurement technology for U & I	RMS-measurement (true RMS value)
Test points	PE probe 1 ↔ PE/GB in the test socket or PE/GB probe 1 ↔ PE/GB probe 2

Insulation resistance test

TEST VOLTAGE

Test voltage	100 – 1000 V DC, adjustable in steps of 10 V
Voltage regulation	Automatic electronic constant-voltage regulation with undervoltage monitoring
Adjustment	Default value +10 V
Measurement accuracy	±1 % of the measurement range end value

CURRENT

Test current max.	5 mA DC – safety current limitation
Test-current measuring range	Measurable and evaluable up to 1 mA
Output power	Max. 0.5 W

RESISTANCE

Measuring range	200 kΩ – 30 MΩ
Resolution	10 kΩ
Measurement accuracy	±1 % of the measurement range end value, ±10 kΩ at a test voltage of at least 500 V

EVALUATION

Resistance limit IR _{Rmax}	1 – 20 MΩ freely selectable, test values equal to or larger than this limit are GO
Undervoltage	If the test voltage is smaller than the default value, the test result is NO GO.

GENERAL INFORMATION

Test timer	0.5 – 60 s in steps of 0.1 s
Measurement technology for U & I	Average measurement
Discharge	≤200 ms – at a DUT with pure ohmic load Precondition: after the test, the test leads still need to be connected to the DUT during the discharge process.
Internal resistance	330 kΩ for IR with max. 1000 V test voltage The internal resistance determines the charging time of your DUT. Min. charging time = internal resistance x DUT capacity [s]
Test points	L&N ↔ PE in the test socket or L&N ↔ test probe 1

High-voltage test DC

TEST VOLTAGE

Test voltage	100 – 2500 V DC, adjustable in steps of 10 V
Voltage regulation	Automatic electronic constant-voltage regulation with under-voltage monitoring
Adjustment	Default value +10 V
Measurement accuracy	±1 % of the measurement range end value

CURRENT

Test current max.	5 mA DC – safety current limited
Output power	Max. 0.5 W
Measurement accuracy	±1 % of the measurement range end value, in the range up to 1 mA

RESISTANCE

Measuring range	200 kΩ – 30 MΩ Test voltage 500 V >> resistance measurement starting at 1 MΩ Test voltage 1000 V >> resistance measurement starting at 2 MΩ Test voltage 2000 V >> resistance measurement starting at 8 MΩ Test voltage 2500 V >> resistance measurement starting at 12.5 MΩ
Resolution	10 kΩ
Measurement accuracy	±2 % of final value ±10 kΩ at a test voltage of at least 500 V

EVALUATION

Resistance limit IR_{Rmax}	1 MΩ – 20 MΩ freely definable, test values equal to or larger than this limit are GO
Undervoltage	If the test voltage is smaller than the default value, the test result is NO GO.

GENERAL INFORMATION

Test timer	0.5 s, 0.6 s, 0.7 s ... 160 s in steps of 0.1 s
Measurement technology for U & I	Average measurement
Discharge	≤200 ms – at a DUT with pure ohmic load Precondition: after the test, the test leads still need to be connected to the DUT during the discharge process.
Internal resistance	330 kΩ for IR with max. 1000 V test voltage The internal resistance determines the charging time of your DUT. Min. charging time = internal resistance x DUT capacity [s]
Test points	L&N ↔ PE in the test socket or L&N ↔ test probe 1

Function test

TEST VOLTAGE

Test voltage	230 V AC single-phase, voltage directly from mains supply
Voltage measurement	No voltage measurement

CURRENT

Test current	2 A AC maximum continuous current
resolution	1 mA
Current measurement and evaluation	True RMS
Measurement accuracy	±1 % of the measurement range end value, ±10 mA

EVALUATION

Upper & lower limit ±tolerance in % from default value	Current: 0 – 2 A, test values within the tolerance limits are GO
Short-circuit detection	Integrated fuse accessible from the bottom
Fault detector	Optically and acoustically

GENERAL INFORMATION

Test timer	0.5 – 10 s in steps of 0.1 s
------------	------------------------------

Alternative method (Substitute leakage current test)

TEST VOLTAGE

Test voltage	approx. 40 – 60 V AC single-phase
Calculated test voltage	230 V
Measurement accuracy	±1 % of the measurement range end value, based on 100 V

LEAKAGE CURRENT

Leakage current I_{eff}	max. 20 mA
Resolution	1 mA
Accuracy	±1 % of the measurement range end value, ±1 mA
Calculated test current	1 mA – 20 mA
Test method	Ground leakage current, enclosure leakage current
Standards	DIN VDE 0701-0702
Test points	L+N ↔ PE, L+N ↔ test probe 1

EVALUATION

Upper limit	0 – 20 mA
-------------	-----------

More information

For further information please visit our homepage www.schleich.com

RoHS conformity

We declare the conformity of our products with the **RoHS2 directive 2011/65/EU** of the European Parliament and of the Council of June 8, 2011 on the restriction of the use of hazardous substances in electrical and electronic equipment, as well as conformity with the **extended delegated directive 2015/863/EU** from March 31, 2015, effective July 22, 2019.

REACH conformity

As a manufacturer of electronic products, SCHLEICH GmbH is a so-called "downstream user" within the meaning of 'REACH'. SCHLEICH GmbH is not subject to any obligations arising from the manufacture and placing on the market of substances/chemicals for pre-registration or registration (ECHA). Our products supplied to customers are "articles" and therefore not to be defined as "substance" or "preparation" (in accordance with Article 3 Definitions). Furthermore, under normal and reasonably foreseeable conditions of use, no substances should be released from the products purchased by customers. Therefore, SCHLEICH GmbH is neither subject to the registration obligation nor to the obligation to prepare safety data sheets. In order to keep the supply chain secure and in the interest of maximum product safety, we make sure that our suppliers fulfill all requirements for the materials and substances we use.

Disclaimer

After the editorial deadline, changes may have been made to the product due to continuous further development.

Technical data subject to change without notice. Delivery subject to availability. No guarantee can be given for the completeness, accuracy and currentness of the data and illustrations.

Liability or guarantee for completeness, currentness and correctness of the given data and illustrations excluded.

Reproduced descriptions may be trademarks and/or copyrights, the use of which by third parties for their own purposes may infringe the rights of the owners.

Copyright

All rights reserved, including intellectual property rights.

Stated names can be copyrighted brands or trademarks of the respective company.

The use of these marks by third parties for their own purpose could violate the rights of the owner.

Copyright © SCHLEICH GmbH